















WEIGHT PROTECTION RESISTANT RESISTANT





Model description

- Low Cut laceup type safety shoes
- Padded collar and Tongue, eyelet laceup comfortable design
- Basf PU/PU Outsole,
- high abrasion resistance, shock aborption
- Steel toe caps, Anti static , SRC(SRA+SRB) Slip resistance

MAIN APPLICATION

- Constuction , Building
- Automotives / Car Assembly
- Mechanical Mould, Sheet Metal Stamping,
- Plastic Injection Molding
- Electronics & Computing
- Automation, Engineering , Manufacturing

Shoe Care Information

- Clean of excess dirt to prevent leather from drying
- Wet shoe must be left to dry naturally not under direct sunlight
- Do not submerge in water or chemicals for excessive periods
- Shoe polish will preserve the finish and life time of footwear

Estate and the second s	
SPECIFICATIONS	
Product Reference	L-083
Standard	EN ISO 20345:2011 S1P SRC
Sizes Range	2-13(UK)
Weight (Size7)	470 grams(half pair)
Midsole	Anti puncture/steel plate
Тоесар	200J -Impact Resistance steel toecap
Footbed	Thick comfort EVA, ergonomic anti static
Outsole	Polyurenthane (PU) from Basf, Dural Density extra lightweight, SRC high slip resistance

www.kprsafety.com









