

# Ultranitril 487

## DESCRIPTION AND GENERAL PROPERTIES


- **Material** Nitrile
- **Length (cm)** 32
- **Thickness (mm)** 0.28
- **Wrist** Straight cuff
- **Colour/Color** Green
- **Interior finish** Easy donning treatment
- **Exterior finish** Embossed texture
- **Size / EAN** 7 8 9 10
- **Packaging** 10 pairs/bag - 100 pairs/carton
- **Complementary information** Guaranteed without silicone



## PERFORMANCE RESULTS

Certification category 3

CE 0334



Dexterity EN 420 : 5/5

### Legends

ANSI	CUT RESISTANCE		
	<b>A1</b> ≥ 200 G	<b>A4</b> ≥ 1500 G	<b>A7</b> ≥ 4000 G
	<b>A2</b> ≥ 500 G	<b>A5</b> ≥ 2200 G	<b>A8</b> ≥ 5000 G
<b>CUT</b>	<b>A3</b> ≥ 1000 G	<b>A6</b> ≥ 3000 G	<b>A9</b> ≥ 6000 G

EN 511	COLD HAZARDS
	PERFORMANCE LEVELS
	0-4 0-4 0 or 1
	└ Water permeability
	└ Contact cold resistance
	└ Convective cold resistance

EN 407	THERMAL RISKS
	Heat and fire
	PERFORMANCE LEVELS
	0-4 0-4 0-4 0-4 0-4 0-4
	└ Resistance to large quantities of molten metal
	└ Resistance to small drops of molten metal
	└ Radiant heat resistant
	└ Convective heat resistance
	└ Contact heat resistance
	└ Burning behaviour

### PROTECTION FROM PESTICIDES

ISO 18889	ISO 18889	ISO 18889
<b>G1</b>	<b>G2</b>	<b>GR</b>

### MICRO-ORGANISMS

EN ISO 374-5	EN ISO 374-5
<b>Protection against bacteria, fungi</b>	<b>Protection against bacteria, fungi, virus</b>
	<b>VIRUS</b>

### CHEMICAL RISKS

EN ISO 374-1	EN ISO 374-1	EN ISO 374-1
<b>Type A</b>	<b>Type B</b>	<b>Type C</b>
<b>U V W X Y Z</b>	<b>X Y Z</b>	
<b>A</b> Methanol	<b>J</b> n-Heptane	
<b>B</b> Acetone	<b>K</b> Sodium hydroxide 40%	
<b>C</b> Acetonitrile	<b>L</b> Sulphuric acid 96%	
<b>D</b> Dichloromethane	<b>M</b> Nitric acid 65%	
<b>E</b> Carbon Disulfide	<b>N</b> Acetic acid 99%	
<b>F</b> Toluene	<b>O</b> Ammonia 25%	
<b>G</b> Diethylamine	<b>P</b> Hydrogen peroxide 30%	
<b>H</b> Tetrahydrofuran	<b>S</b> Hydrofluoric acid 40%	
<b>I</b> Ethyl acetate	<b>T</b> Formaldehyde 37%	

### RADIOACTIVE CONTAMINATION



### ELECTROSTATIC DISCHARGE PROTECTION



### EN 388 MECHANICAL HAZARDS



PERFORMANCE LEVELS
0-4 0-5 0-4 0-4 A-F (P)
└ Impact protection
└ Cut resistance according to ISO 13997
└ Puncture resistance
└ Tear resistance
└ Blade cut resistance
└ Abrasion resistance

For more details: [www.mapa-pro.com](http://www.mapa-pro.com)

**MAPA**<sup>®</sup>  
PROFESSIONAL

[www.mapa-pro.com](http://www.mapa-pro.com)

## SPECIFIC ADVANTAGES

- Freedom of movement and excellent sensitivity, due to the gloves reduced thickness
- Chlorinated finish for better protection of the products being handled

## MAIN FIELDS OF USE

### Automotive/mechanical industry

- Spray-painting

### Mechanical industry

- Machining parts using cutting oil
- Precision assembly
- Assembly of small oily parts

## INSTRUCTIONS FOR USE

### Instructions for use

- It is recommended to check that the gloves are suitable for the intended use, because the conditions of use at workplace may differ from the "CE"-type tests.
- Persons sensitized to dithiocarbamates and thiazoles should not use these gloves.
- Put the gloves on dry, clean hands.
- Do not use the gloves in contact with a chemical for a duration in excess of the measured breakthrough time. Refer to the website [www.mapa-pro.com](http://www.mapa-pro.com) or contact the Technical Customer Service - MAPA PROFESSIONNEL ([stc.mapaspontex@mapaspontex.fr](mailto:stc.mapaspontex@mapaspontex.fr)) in order to know this breakthrough time. Use 2 pairs alternatively when in long duration contact with a solvent.
- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm.
- Inspect the gloves for cracks or snags before reusing them.

### Storage conditions

- Store the gloves in their original packaging protected from light, humidity and heat.

### Laundering conditions

- Before taking off the gloves, clean them as appropriate :
- in use with paints, pigments and inks : wipe with a clean cloth dampened
- with a suitable solvent, and rub over with a dry cloth
- in use with a solvent (diluent, etc...) : rub over with a dry cloth
- in use with acids or alkalies : thoroughly rinse the gloves under running water, and rub over with a dry cloth
- Caution : improper use of the gloves or submitting them to any cleaning or laundering process can alter their performance levels.

### Drying conditions

- Ensure the inside of the gloves is dry before putting them on again.

## LEGISLATION

This product is not classified hazardous according to the regulation (EC) n°1272/2008 of the European Parliament and of the Council. This product does not contain more than 0.1 % of substance of very high concern (SVHC) or any substance included in the annex XVII of the regulation n° 1907/2006 of the European Parliament and of the Council (REACH).

- **UE type certificate or CE type examination certificate** : 0075/014/162/10/18/2078
- **Issued by the notified body nr** : 0075 - C.T.C. – 4 rue Hermann Frenkel - F- 69367 LYON Cedex 07
- **Quality assurance certificat** : 0334 Asqual 14 rue des Reculettes -F-75013 PARIS